

BMT Hot Melt Extruders



✓ Standard + Option ✗ NA

Machine Features

- Digital readout of all temperature zones.
- Under temperature on all zones.
- Programmable temperature controls which can be programmed to any make of Hot melt blocks.
- Positive displacement gear type pump.
- Progressive sealant heating hopper, pump hose and gun.
- Tamper proof factory set operating temperatures.
- 'Cool to touch' moulded gun handle.
- Miniature circuit breaker protection.

Technical Data

	BMT1000	BMT 2000	BMT 3000	BMT 4000
Production Capacity Approx.	80-100 Units in 8-10 hrs	160-200 Unit in 8-10 hrs	250-300 units in 8-10 hrs	350-400 units in 8-10 hrs
Material Output	1kg/min	2kg/min	3kg/min	4kg/min
Hopper Size	30kg	50 Kg	75Kg	125kg
Temperature controller	3	4	4	4
Programmable 7 Days timer	+	✓	✓	✓
Hose Length	3m	3m	3m	3m
Length	720mm	880mm	1020mm	1120mm
Width	420mm	570mm	570mm	750mm
Height	970mm	1240mm	1370mm	1650mm
Weight	150 kg	250 kg	400 kg	450 kg
Voltage	220V/240	V220V/240V	220V/240V	220V/240V
Frequency	50/60Hz	50/60Hz	50/60Hz	50/60Hz
Power	2.2Kw/10 Amps	3 kw/13Amps	3.5Kw/15 Amps	4.8kw/20Amps

BMT Press Table / Clamp Table



✓ Standard + Option ✗ NA

Machine Features

- Clamping action is controlled by a conveniently situated foot pedal.
- Fully adjustable rise and fall speed.
- Unique design allows any length of glass to be sealed efficiently.
- Hard wearing swivel castors allow maximum rotation with minimum effort.
- Clamping Gap: Up to 42mm (cushioned by heavy industrial rubber).
- Fully adjustable jaw pressure.
- Open Ended Jaw.
- Multi-Directional Rollers.
- Air operated.

Technical Data

Note :- Any non-standard sizes can be manufactured to suit customers requirements.

	BMT-PT-1010	BMT-PT-1515	BMT-PT-2015	BMT-PT-3020
Glass Size	1000mmX 1000mm	1500mmX1500mm	2000mmX1500mm	3000mmX 2000mm
Length	1050mm	1550mm	1550mm	2050mm
Width	1050mm	1550mm	2050mm	3050mm
Height	900-950mm	900-950mm	900-950mm	900-950mm
Weight	80kg	120kg	150kg	250kg
Air Pressure	6 Bar	6 Bar	6 Bar	6 Bar
Foot Pedal	✓	✓	✓	✓